2020 Integrated Factory Solution Developing and Perfecting Your Own Factory



www.ieiworld.com

IEI Integrated Factory Automation Solution

Developing and Perfecting Your Own Factory

IEI's integrated factory solution improves the production efficiency and warehouse management accuracy. To catch the wave of automatic assembly, robot system will be a major role along with the machine vision and motion control solutions. For factory automation control terminals, IEI offers industrial computing solutions with robust IP65 design, wide temperature, and flexible add-on card expansion. To elevate the efficiency of warehouse management, IEI provides UHF RFID and 1D/2D barcode reader solutions with various form factors.



Intelligent Energy Management

IEI industrial machines can immediately transmit essential operating data — including energy consumption and status. This adds a continuous stream of useful data for plant managers and industrial engineers that can be mined across a facility's machines to detect key trends and worrisome failures. In other words, vital micro machine data gets aggregated into a valuable macro view of a facility.



Warehouse Management System

One big trend in the future is the introduction of "transport systems" in the warehouse. The autonomous vehicles which can sense their surroundings independently using laser scanners, infrared sensors, and RFID chips, and navigate to their respective destinations autonomously.

The autonomous vehicles (autonomous transport robots) can travel on a track, form the basic elements of the solution. The panel PC, mobile computer and embedded computers form the entire control system.



Automatic Manufacturing Solution

Currently, the manufacturing industry is moving towards the goal of Industry 4.0-Smart Factory. From IT to OT, IEI provides a complete IIoT solution to assist customers in digital transformation and enhance market competitiveness.

• Machine Vision Solution

Machine vision is the process of applying a range of technologies and methods to provide imaging-based automatic inspection, process control, robot guidance and more.



• MES/NAS

Al Inference System in Smart Factory

Artificial Intelligence, AI, is changing our lives from the past to the future. It enables machine learning by using a variety of training models to simulate and infer the status or appearance of objects. Vision Analytics on the factory floor adds intelligence to factories design and process. Today's technologies automate the collection, storage, retrieval, and decision making across multiple factories and factory sub-systems at the edge.

Deep Learning and Inference

Deep learning is part of the machine learning method. It allows computational models that are composed of multiple processing layers to learn representations of data with multiple levels of abstraction. Deep neural network and recurrent neural network architectures have been used in applications such as object recognition, object detection, feature segmentation, text-to-speech, speech-to-text, translation, etc. In some cases the performance of deep learning algorithms can be even more accurate than human judgement.



Intel[®] Distribution of OpenVINO[™] toolkit

Intel[®] Distribution of OpenVINO[™] toolkit is based on convolutional neural networks (CNN), the toolkit extends workloads across multiple types of Intel[®] platforms and maximizes performance.

It can optimize pre-trained deep learning models such as Caffe, MXNET, and Tensorflow. The tool suite includes more than 20 pre-trained models, and supports 100+ public and custom models (includes Caffe*, MXNet, TensorFlow*, ONNX*, Kaldi*) for easier deployments across Intel[®] silicon products (CPU, GPU/Intel[®] Processor Graphics, FPGA, VPU).



IEI AI Ready Solution Accelerates Your AI Initiative

The FLEX-BX200 and TANK-870AI Dev. Kit are AI hardware ready system ideal for deep learning inference computing to help you get faster, deeper insights into your customers and your business. IEI's FLEX-BX200 and TANK-870AI Dev. Kit support graphics cards, Intel[®] FPGA acceleration cards, and Intel[®] VPU acceleration cards, and provide additional computational power plus end-to-end solution to run your tasks more efficiently. With the Intel[®] OpenVINO toolkit and NVIDIA TensorRT, it can help you deploy your solutions faster than ever.



• Machine Vision for Sorting and Grading of Agricultural Products

Agricultural products are valued by their appearance. The color indicates parameters like ripeness, defects, etc. The quality decisions vary among the graders and often inconsistent. Machine vision technology offers the solution for all these problems.

The FLEX series designed for machine vision market has four PCIe 3.0 expansion slots for installing motion controller cards, GP GPU/ FPGA/VPU cards and the PoE Ethernet card which is developed by IEI and has four GbE Power over Ethernet (PoE) ports compliant with IEEE 802.3af for direct connection to CCTV cameras without needing separate power.



AOI Defect Classification

During the manufacturing process, defects could be introduced and harmful to the quality. It is necessary to classify the defects detected by AOI machine appropriately especially killer defects. The higher accuracy to classify defects, the less cost spent on review and repair station. The TANK AIoT Dev. Kit features rich I/O and dual PCIe x8 signals to support add-ons like the acceleration cards (Mustang-F100-A10 & Mustang-V100-MX8) or the PoE to enhance defect detection performance.



Intelligent Manufacturing Solution

Currently, the manufacturing industry is moving towards the goal of Industry 4.0-Smart Factory. From IT to OT, IEI provides a complete IIoT solution to assist customers in digital transformation and enhance market competitiveness.

In the IT, mainly to assist customers to achieve the intelligent management, the "MIoT Intelligent Management System" and "QVR Intelligent Imaging System" of IEI Group provide "manufacturing information" and "image information" timely at the manufacturing site and calculate OEE with the AI calculation analysis that help customers greatly improve the operation efficiency of the factory and meet the needs of future factory intelligent management.

In the OT, we mainly assist customers to quickly upgrade from the traditional PLC control system to the intelligent control system. We provide the high-precision "PC-Based Motion Controller" and integrate the vision module and the IoT module to establish the intelligent application controllers, such as "intelligent dispensing controller" and "robot controller". In addition, We also provide independent-development intelligent mobile platforms, AMR control system and multi-axis industrial robots, to help the factory to achieve automation and labor saving.



Intelligent dispensing controller

MOTORCON's intelligent dispensing controller integrates four major features, including:

Integrated controller, high speed and high precision, visual computing function and dispensing technics. And it can be used in a variety of dispensing applications, such as: shoe material dispensing, headlights dispensing, printed circuit board dispensing, etc.





Integrated controller

Use PC-Based architecture to integrate IPC, motion control card, servo wiring board, I/O card and I/O wiring board. Therefore, it has the advantages of small size and high stability; it can integrate diverse software systems, including motion control systems, vision systems and IoT systems.



High speed and high precision

According to the different needs of the manufacturer's application field, MOTORCON develops a continuous smooth curve function. Under the synchronous speed of 230mm/s, the maximum error of the trajectory is less than 0.7mm, which helps the manufacturer to maintain a certain precision under the condition of increasing production capacity.

Visual computing function



Dispensing technics

- Point, coating, irrigation, and glue processing settings
- Glue gun calibration and processing height measurement function
- · A variety of clear gun mechanisms
- DXF track generation
- A variety of drawing functions
- Precise servo supply control function

12				01W18
1.0:05(0.00(mm/s)	80	15.8E.00.0 82(ma)		
2.387.05.00mm/s)	100	16.80950 (ms)	0	
s.lasbitit(ma)	200	17.9'2 # MAR(ma)		
4. Feb(8. T0mm/s)	25	18.82424242	SACE -	
5.(Fibbold/Kom)	100	19.8241.828	1.000	
6.5(12)8.8(mm/s)	20	20 M = AK	•	
7.50 fiz.latiktirews)	300	21.22.0000000	9	
8.332.677.22	0	22.R#EWAN		
9. BEC HEFE Met (me)	1500	23.82#RR.84		
10.至工業位用器	D	24.MT.R.R.W.#	88 ·	
11.空闲港区州副(m)	0	25.加工管师投稿	1.不抽起 •	
12.12 FEB EV1FICes)	9	26.89%Alttom	25.000	
13.世界地投伏法(m)		27.8141-0.2212		0,0,0
14.15天田田川校(m)	0			保存

Autonomous Mobile Robot (AMR/AGV)

- According to customer needs, you can purchase [complete vehicle] or [controller] and interact with the customer's car
- · Stacked structure design to add the dedicated device to the AMR, up to 100 kg
- MOTORCON motion controller combines with Linux + ROS architecture, integrates 2D Lidar/IMU/Encoder, builds the electronic map and self-positioning calculation, and helps AMR independently plan the path and detect obstacles.
- Further development: developers can quickly import system without having to develop from scratch, which greatly reduces development time.
- No extra track setting, autonomous planning path and detecting obstacles are needed; lower development cost greatly.
- Actual hardware device: customers no longer need to verify the developed program through the simulator.





* Factory automation combined with AMR to create a fully automated processing system

Motion controller

Integrated motion controller has several features, including small size, superior stability, IoT, machine vision, PC-based, and integrates with intelligent software, sensor processing software and customized process application development service, which extends a variety of intelligent controllers, such as: intelligent dispensing controller, autonomous mobile robot, etc. In addition, we also provide EtherCAT motion controller, which supports multiple brands of EtherCAT motors and components, and it can control up to 64 axes. EtherCAT also provides pre-tune-up software which can be used in the field to deploy drivers and adjust the parameters according to different requirements.



• MIoT intelligent manufacturing management system

The challenges of current manufacturing facing

- Can't effectively manage the order production progress, causing unstable product quality.
- Adopting lagging indicator results in failing to respond the problem of production line in time, so the timing of correction is missed.
- The equipment history information is hard to read and equipment can't be maintained.
- Using traditional manual copying information without an equipment management system is easily to cause errors.
- Lack of effective tools to assist personnel management and work order management.



7

Machine Vision Solution

Machine vision is a replacement for human vision and judgment by using video cameras, software and computers to perform an inspection task, such as gauging, counting as well as barcode and optical character reading (OCR). IEI designs and develops advanced barcode readers and embedded computers, which can be used to perform reliably at higher speed and with greater precision.



Inspection & Verification

Industrial cameras can stably transfer data to PC while in continuous shooting, enabling it to become a reliable and high compatibility platform.





Pattern Matching



Packing Inspection







Defect Detection



Barcode Reading



Image Gauging

Analysis

Product Selection



TANK-870e-H110

TANK-870-Q170 TANK-880-Q370





IMBA-Q370





IMBA-Q170-i2

IMBA-H110

DM-F Series

Advanced Controller Applications

- Quality Checking
- Subassembly Verification
- Packing Inspection

• IoT High Speed Barcode Reader

Installing ITDB Series barcode reader with QNAP NAS system allows you to manage your production lines in a more efficient way. The NAS can act as a private cloud or a public cloud. An ITDB system that runs over an IP network infrastructure enables the decoded images and results to be distributed to any number of sites, within the constraints of available bandwidth.





Intelligent Energy Management

With a growing interest in renewable energy resources globally, the sun and the wind have become one of the most rapidly growing eco-friendly alternative energy sources in the recent years.

By using solar thermal panels and wind turbines, both sunlight and wind are transformed into electricity ready to be consumed at factory and any other establishments that require electricity. These two will be the most important power production units of any hybrid system up to date.

Information about power production and consumption will be collected and used by the control unit to create profiles of power consumption/ production for each source/load of the system. Once these profiles are created a better and tighter management can be deployed.



Energy Data Collection & Analysis

Information technology adds intelligence to factories from design to the end of the process. Today's technologies automate the collection, storage and retrieval of data from across multiple factories and factory sub-systems to make that data available for decision makers, from facility managers to supervisors.



Warehouse Management System (WMS)

Material input/output management and examination are the duty of a warehouse. As quantity inconsistency is the most common problem in handwritten vouchers, personnel will be unable to capture the exact quantity of material input, shipping, and stock and implement first in first out (FIFO) control. Even worse, personnel will need to spend more time on finding raw materials, and can not trace incoming materials effectively. IEI thus introduces Warehouse Management System (WMS) to provide convenient and traceable management through cloud computing. The benefits of the WMS include:

- Ensure traceability for raw material input and product shipping.
- Shorten material selection and shipping time.
- Enhance warehouse management efficiency and accuracy.
- Ensure real-time warehouse information.
- Minimize customer complaints from man-induced mistakes.
- Enable real-time capture of fleet status and enhance vehicle dispatch flexibility.



Smart Warehouse Management Solutions

Deliveryman can scan the delivery receipt through the barcode reader to upload goods data back to the goods management system for instant update.









The warehouse personnel can use the barcode reader to scan barcodes of stock-ins and stock-outs information then upload the stock data to the inventory management system for instant update.



The AFL3/INOX/PPC-F/UPC panel PCs support wide-range operating temperature so that they can be deployed in any high- or low-temperature warehouses.



Fleet Logistics Applications

Fleet management and dispatching efficiency can be improved by taking the advantages of the 3G connection of the IKARPC and AFOKAR panel PC to send real-time information to the dispatching center for confirming vehicle locations (GPS) and driving conditions (OBD-II). The IVS series in-vehicle computer is designed with reliable performance for harsh environments. Rich I/O ports are provided to connect with multiple peripheral devices in vehicle for different applications.



Incoming Materials

After completing the IQC inspection, the system generates an ID for raw materials. This ID enables users to trace the supplier, material incoming date, IQC inspection results, and supplier lot number. Warehouse personnel can retrieve information from their mobile devices, including the storage lot of raw materials and route instruction, to facilitate slotting raw materials.

Shipping Activities

Mobile devices provide picking personnel shipping list to manage picking by picking sequence, by picking route, and by FIFO. When shipping products with pallets, mobile devices will collect the product ID on the shelve using RFID technology to record the shipping order and transportation information.



Warehouse Management

• Receiving/Dispatching Materials

Receiving

Handheld device application: After receiving goods and signing on the delivery man's handheld device, the cloud-based inventory management system will be updated in real time.

Receiving/Dispatching

- » AFL3/PPC-F series with barcode reader can be used to scan the barcode of the incoming/outgoing package
- » Data can be uploaded to the cloud immediately



Warehouse Management: Inbound/Outbound

- Automation system for scanning incoming/outgoing goods
- Warehouse security monitoring



Fleet Management

- GPS for vehicle tracking
- 3G/4G capability for data transmission
- OBD-II interface for vehicle diagnosis



Remote Management



Server-Side Software

IKARPC-W10A

GPS 1

AFOKAR-08A

IVS-300-ULT3/IVS-300-BT

13

MES

MES Software System Solution

Most manufacturing industries require a lot of labor work in production, production line and equipment management, and production data collection. While modern manufacture-based enterprises need to face land acquisition difficulty, labor cost rise, and labor recruitment difficulty, new employees who are not familiar with production operation will increase defect rate. How to implement effective control has become a real problem to many manufacture-based enterprises.

Advantages of smart solutions

- » Enable process management and optimization. Increase product tractability.
- » Provide production scheduling and effective management for production quantity.
- » Provide electronic SOPs to enhance product yield rate.
- » Ensure equipment management and integration for effective labor hour management and equipment availability.
- » Implement automation to reduce labor costs and stabilize production rhythm.

Smart operation

- » ID creation: After IQC inspections, an ID (barcode or RFID) is assigned to the material to accelerate information collection and accuracy in the production process.
- » Information analysis: Production data is digitized for production scheduling and management to generate realtime data regarding schedule accomplishment rate, quality report, and production.
- » Automatic material replenishment: Materials are fed to each station by means of the AGV system to reduce storage space on the production line.
- » Electronic SOP: Provide clear and correct SOPs to each station to ensure the correct version is in place.
- » Equipment monitoring: Integrate data of production equipment, monitor equipment status, and provide equipment parameters.
- » Robotic arm: Assists in routine handling operation and stabilize production pace.
- » Quality management: Measure product quality after production and manage product quality analysis.

Production record

Products are effectively recorded during production with traceability to their in-process quality analysis, installed parts and components, suppliers and customers, and transportation methods.

Product Selection

» TANK-800 & FLEX-BX200 Series



TANK-800 series



RFID

ID creati

Eauip

FLEX-BX200 Series

Informatio

analy

Applications

Qualit

» Industry Workstation

• AFL3 PoE Panel PC

						00	
Model Name	AFL3-W07A-AL	AFL3-W10A-AL	AFL3-12A-AL	AFL3-W15A-AL	AFL3-W15C-ULT5	AFL3-W19C-ULT5	AFL3-W22C-ULT5
LCD Size	7"	10.1"	12.1"	15	i.6"	18.5"	21.5"
Resolution	1024 x 600 (16:9)	1280 x 800 (16:10)	1024 x 768 (4:3)		1366 x 768 (16:9)		1920 x 1080 (16:9)
Touch Screen	Projected	capacitive with USB inte	erface (anti-UV / anti-glar	e coating)	Projected capac coating)	itive with USB interface (anti-UV / anti-glare
CPU	Intel [®] Celeron N3350 (2M Cache, up to 2.4 GHz) TDP 6W	Apollo lake Celeron® Pr	rocessor J3455 (2M Cac 10W	ne, up to 2.3 GHz) TDP	Intel Whiskey Intel [®] C 4.10 GHz (TDP15W)	ore™ i5-8365UE Proces	sor 6M Cache, up to
I/O Ports & Switch	2 x GbE LAN (LAN1 on-board PoE at) 2 x USB 3.2 Gen 1 2 x USB 3.2 Gen 1 1 x 12 DC jack 1 x power switch 1 x Reset button 1 x Clear CMOS button 1 x AT/ATX switch	1 x RS-232/422/485 by RJ-45 1 x RS-232 by DP9 2 x GbE LAN (LAN1 option PoE bt PD module) 2 x USB 3.2 Gen 1 2 x USB 3.2 Gen 1 2 x USB 2.0 1 x HDMI output 1 x 9V ~ 30V DC jack 1 x power switch 1 x Line out 1 x Reset button 1 x Clear CMOS button			2 x PoE GbE LAN (optioal EEE802.3af/at/bt) 1 x GbE LAN 4 x USB 3.1 Gen.2 1 x HDMI output 1 x RS232/422/485 1 x RS232 1 x 12V DC jack 1 x power switch 1 x AT/ATX switch 1 x Clear CMOS button		
Front Panel Construction				PC + ABS Plastic			
PoE Option	on-board IEEE802.3 at			IEEE8	02.3 bt		
Mounting	Panel, Wall, Sta VESA 75	and, Arm, Rack x 75 mm	Panel, Wall, Racl VESA 75 x 75 mr	<, Stand and Arm n / 100 x 100 mm	F VES	Panel, Wall, Stand and Ar A 75 x 75 mm / 100 x 10	m 0 mm
Operating Temperature (°C)	-20°C ~ 50°C (Ambient with air flow)	-10°C ~ 50°C (Ambient with air flow)		-20°C	~ 50°C (Ambient with a	ir flow)	
Storage Temperature (°C)				-20°C ~ 60°C			
IP Level	IP 65 compliant front panel	IP 65 compliant front panel IP 64 compliant front panel					
Thermal Solution				Fanless			
Power Requirement	12V only		9V - 30V			12V only	

• AFL3 Series Panel PC

Model Name	AFL3-W07A-BT	AFL3-08A-BT	AFL3-W10A-BT	AFL3-12A-BT	AFL3-12C-ULT3
LCD Size	7"	8.4"	10.1"	12	1"
Resolution	1024 x 600 (16:9)	800 x 600 (4:3)	1280 x 800 (16:10)	1024 x 7	768 (4:3)
Touch Screen	Projected capacitive with USB interface (anti-UV / anti-glare coating)	5-wire resistive with RS-232 interface (anti-glare coating) Projected capacitive with USB interface (anti-UV / anti-glare coating)	Projected capacitive with USB interface (anti-UV / anti-glare coating)	5-wire resistive with RS-232 interface (anti-glare coating) Projected capacitive with USB interface (anti-UV / anti-glare coating)	Projected capacitive with USB interface (anti-UV / anti-glare coating)
CPU	Intel [®] Celeron [®] N2807 (dual core, 1.58 GHz)	Intel [®] Celeron [®] J1900 (quad core, 2.0 GHz)	Intel [®] Celeron [®] J1900 (quad core, 2.0 GHz)	Intel [®] Celeron [®] J1900 (quad core, 2.0 GHz)	Intel [®] Core™ i5 and Celeron [®] ULT Processor
I/O Ports & Switch	2 x RS-232 COM port (DB-9 connector) 2 x USB 3.2 Gen 1 2 x GbE LAN 1 x Power switch 1 x Reset button 1 x AT/ATX switch 1 x 9-30V Lockable power jack	1 x RS-232 COM port (RJ-45 connector) 1 x RS-232/422/485 COM port (DB-9 connector) (RI/5V/12V) 2 x USB 3.2 Gen 1 2 x RJ-45 for GbE LAN 1 x Power switch 1 x Audio port (line-out) 1 x Reset button 1 x AT/ATX switch 1 x 9-30V DC Lockable power jack	1 x RS-232 COM port (RJ-45 connector) 1 x RS-232/422/485 COM port (DB-9 connector)(RI/5V/12V) 2 x USB 3.2 Gen 1 2 x USB 2.0 2 x RJ-45 for GbE LAN 1 x Power switch 1 x Audio port (line-out) 1 x Reset button 1 x AT/ATX switch 1 x 9-30V DC lockable power jack	1 x RS-232 COM port (RJ-45 connector) 1 x RS-232/422/485 COM port (DB-9 connector)(R/5V/12V) 2 x USB 3.2 Gen 1 2 x USB 2.0 2 x RJ-45 for GbE LAN 1 x Power switch 1 x Audio port (line-out) 1 x Reset button 1 x AT/ATX switch 1 x 9-30V lockable power jack	1 x RS-232/422/485 (DB-9) 1 x RS232 (RJ-45) 2 x GbE LAN 2 x USB 2.0 2 x USB 3.2 Gen 1 1 x DC jack (12-30V DC) 1 x HDMI 1 x Power switch 1 x Reset button 1 x AT/ATX switch
Front Panel Construction			PC + ABS Plastic		
Mounting		Panel, Wall, Stand, Arm, Rack VESA 75 x 75 mm		Panel, Wall, Rac VESA 75 x 75 m	k, Stand and Arm n / 100 x 100 mm
Operating Temperature (°C)	-20°C ~ 50°C (Ambient with air flow)	-15°C ~ 55°C (Ambient with air flow)	-10°C ~ 50°C (Ambient with air flow)	-20°C (Ambient w	~ 50°C ⁄ith air flow)
Storage Temperature (°C)	-20°C ~ 60°C	-20°C ~ 65°C -20°C ~ 60°C			
IP Level	IP 65 compliant front panel IP 64 compliant front panel				
Thermal Solution	Fanless				
Power Requirement			9 V ~ 30 V		





-1

Model Name	AFL3-W15A-BT	AFL3-W15B-H81	AFL3-W15C-ULT3	AFL3-W19C-ULT3	AFL3-W19A-AL	AFL3-W22C-ULT3
LCD Size		15.6"		18	3.5"	21.5"
Resolution			1366 x 768 (16:9)			1920 x 1080 (16:9)
Touch Screen	5-wire resistive with RS-23 Projected capacitive with L	2 interface (anti-glare coatin ISB interface (anti-UV / anti-	g) glare coating)	Projected capacitive with USB interface (anti-UV / anti-glare coating)	5-wire resistive with RS-23 coating) Projected capacitive with L glare coating)	2 interface (anti-glare ISB interface (anti-UV / anti-
CPU	Intel [®] Celeron [®] J1900 (quad core, 2 GHz)	Intel [®] Core™ i7/i5/i3, Pentium [®] , Celeron [®] processor (TDP 35W)	6 th Generation Intel [®] Core ™ i5 and Celeron [®] on-board processor	Intel [®] Core [™] i5 and Celeron [®] ULT Processor	Intel [®] Celeron [®] J3455 (quad core, 1.5GHz up to 2.3GHz)	Intel [®] Core™ i5 and Celeron [®] ULT Processor
I/O Ports & Switch	1 x RS-232 COM port (RJ-45 connector) 1 x RS-232/422/485 COM port (DB-9 connector) (RI/SV/12V) 2 x USB 2.0 2 x USB 3.2 Gen 1 2 x GbE LAN 1 x Power switch 1 x Reset button 1 x AT/ATX switch 1 x Audio port (line-out) 1 x 9-30V lockable power jack	1 x RS-232 COM port (DB-9 connector) 1 x RS-232/422/485 COM port (DB-9 connector) (RI/5V/12V) 2 x GbE LAN 4 x USB 3.2 Gen 1 1 x HDMI output 1 x Power switch 1 x AESE button 1 x AT/ATX switch 1 x AUdio port (line-out) 1 x 9-30V lockable power jack	1 x RS-232 by DB-9 (RI/5V/12V) 1 x RS-232/422/485 by DB-9 (RI/5V/12V) 2 x GbE LAN 4 x USB 3.2 Gen 1 1 x HDMI output 1 x Power switch 1 x Reset button 1 x AT/ATX switch 1 x 9-30V lockable power jack	1 x RS-232 by DB-9 (RI/5V/12V) 1 x RS-232/422/485 by DB-9 (RI/5V/12V) 2 x GbE LAN 4 x USB 3.2 Gen 1 1 x HDMI output 1 x Power switch 1 x Reset button 1 x AT/ATX switch 1 x 9-30V lockable power jack	1 x RS-232/422/485 by RJ-45 1 x RS-232 by RJ-45 2 x GDE LAN 2 x USB 3.2 Gen 1 2 x USB 2.0 1 x HDMI output 1 x 12V \sim 34V DC jack 1 x Power switch 1 x AT/ATX switch 1 x Line out	1 x RS-232 by DB-9 (R/55//12V) 1 x RS-232/422/485 by DB-9 (R/55//12V) 2 x GbE LAN 4 x USB 3.2 Gen 1 1 x HDMI output 1 x Reset button 1 x Reset button 1 x AT/ATX switch 1 x 9-30V lockable power jack
Front Panel Construction			PC + AE	3S Plastic		
Mounting	Panel, Wall, Rack, Stand and Arm VESA 75 x 75 mm / 100 x 100 mm			Panel, Wall, Stand and Arm VESA 75 x 75 mm / 100 x 100 mm	Panel, Wall, Rack, Stand and Arm VESA 75 x 75 mm / 100 x 100 mm	
Operating Temperature (°C) (Ambient with air flow)	-20°C ~ 50°C (Ambient with air flow)				-15°C ~ 50°C (Ambient with air flow)	-20°C ~ 50°C (Ambient with air flow)
Storage Temperature (°C)			-20°C	~ 60°C		
IP Level			IP 64 compli	ant front panel		
Thermal Solution			Far	nless		
Power Requirement		9 V ~	~ 30 V		12 V - 34 V	9 V - 30 V

• PPC-F Series Heavy Industrial Panel PC

	ें सन्त			-); 			
Model Name	PPC-F06B-BT	PPC-F08B-BT	PPC-F10B-BT	PPC-F12B-BT	PPC-F15B-BT	PPC-F17B-BT	PPC-F19B-BT
LCD Size	5.7" (4:3)	8" (4:3)	10.4" (4:3)	12" (4:3)	15" (4:3)	17" (5:4)	19" (5:4)
Resolution	640 (W) x 480 (H)	800 (W)	x 600 (H)	1024 (W)	1024 (W) x 768 (H)		c 1024 (H)
Touch Screen	4-wire resistive type flat touch window, 3H	5-wire resistive type	flat touchscreen, 3H		5-wire resistive type / projected capacitive t	with RS-232 interface ype with USB interface	
Touch Controller		PenMount DMC9000			Penmount EETI E	DMC 9000 XC3000	
CPU	Intel [®] Celeron [®] processor N2807, dual-core, 1.58GHz		Intel [®] Celeron [®] J1900 on-board SoC, quad-core, 2GHz				
I/O Ports and Switches	1 x RJ-45 LAN port 1 x RS-232 COM port (DB-9 connector) (RI/SV/12V) 1 x RS-422/485 2 x USB 3.2 Gen 1 2 x USB 2.0 1 x 9 V \sim 36 V DC lockable jack (2-pin) 1 x Audio port (line- out) 1 x Power switch 1 x Reset button 1 x AT/ATX switch	1 x RS-232 COM port (RJ-45 connector) 1 x RS-232/422/485 COM port (DB- 9 connector) (RI/SV/12V) 2 x USB 3.2 Gen 1 2 x GBE LAN 1 x Power switch 1 x Reset button 1 x AT/ATX switch 1 x Audio port (line- out) 1 x 9 V ~ 30 V lockable power jack	1 x RS-232 COM port (RJ-45 connector) 1 x RS-232/422/485 COM port (DB-9 connector) (RI/5V/12V) 2 x USB 2.0 2 x USB 3.2 Gen 1 2 x GbE LAN 1 x Power switch 1 x Reset button 1 x AT/ATX switch 1 x Audio port (line- out) 1 x 9 V ~ 30 V lockable power jack	2 x RJ-45 LAN port 2 x USB 3.2 Gen 1 2 x USB 2.0 1 x HDMI 2 x RS-232 1 x RS-232/422/485 1 x VGA 1 x 9 V ~ 36 V DC jack (4-pin) 1 x 9 V ~ 36 V DC terminal block 1 x Power switch	2 x RJ-45 LAN port 2 x USB 3.2 Gen 1 2 x USB 2.0 1 x HDMI 2 x RS-232 1 x RS-232/422/485 1 x VGA 1 x 9 V ~ 36 V DC jack (4-pin) 1 x 9 V ~ 36 V DC terminal block 1 x Line-out 1 x Power switch	2 x RJ-45 LAN port 2 x USB 3.2 Gen 1 2 x USB 2.0 1 x HDMI 2 x RS-232 1 x RS-232/422/485 1 x VGA 1 x DC jack (4-pin) 1 x Terminal block 1 x Microphone & speal 1 x Power switch	ker
System Cooling				Fanless			
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)						
Storage Temperature		-20°C ~ 60°C (-4°F ~ 140°F)					

• PPC-F Series Heavy Industrial Panel PC



Model Name	PPC-F15C-Q370	PPC-FW15C-Q370	PPC-F17C-Q370	PPC-FW19C-Q370	PPC-FW22C-Q370	PPC-FW24C-Q370	
LCD Size	15" (4:3)	15.6" (16:9)	17" (5:4)	18.5" (16:9)	21.5" (16:9)	23.8" (16:9)	
Max. Resolution	1024 x 768	1366 x 768	1280 x 1024	1366 x 768	1920 x 1080	1920 x 1080	
Brightness (cd/m ²)	450	400	350	400	250	250	
Touchscreen Type		Projected	capacitive type with 10-po	int multitouch and anti-glar	e coating		
Touch Controller			EETI E	XC3188			
CPU		8 th Generition Intel [®] Core™ i7/i5/i3 porcessors in the LGA 1151 package (Please choose the TDP of the the processor under 65W)					
I/O Ports and Switches	1 x HDMI output 2 x GbE LAN 6 x USB 3.2 Gen 1 Type-A 2 x RS-232 DB-9 type 1 x Mic in			1 x Line out 1 x AC Inlet Power button with power LED (power on=Blue) AT/ATX mode switch Reset button			
System Cooling	Active fan						
Operating Temperature	-10°C ∼ 50°C (with air flow)						
Storage Temperature	-20°C ~ 60°C						
Humidity	10% ~ 95% (non-condensing)						
Power Supply			AC input ATX Input: 100VAC~2	power supply 240VAC, 50/60Hz			



Model Name	PPC-F15D-ULT5	PPC-FW15D-ULT5	PPC-F17D-ULT5	PPC-FW19D-ULT5	PPC-FW22D-ULT5	PPC-FW24D-ULT5
LCD Size	15" (4:3)	15.6" (16:9)	17" (5:4)	18.5" (16:9)	21.5" (16:9)	23.8" 16:9)
Max. Resolution	1024 x768	1366x768	1280x1024	1366x768	1920x1080	1920x1080
Brightness (cd/m ²)	450	400	350	400	250	250
Touchscreen Type		Projected	capacitive type with 10-po	pint multitouch and anti-glai	re coating	
Touch Controller			EETI EXC	3000 Series		
CPU			8 th Genertion Intel [®] Co 8 th Genertion Intel [®] Ce	re™ i5-8365U 4.10GHz leron® 4205U 2.00GHz		
I/O Ports and Switches	4 x USB 3.2 Gen 1 1 x HDMI output 1 x RS-232/422/485 1 x RS-232 2 x PoE GDE LAN (IEEE802.3af/at/bt)			1 x GbE LAN 1 x 12V DC jack 1 x Power switch 1 x AT/ATX switch		
Thermal Solution			Far	lless		
Front Frame			Alum	ninum		
Mounting	Par	nel, Wall, Rack, Stand and VESA 100 x 100 mm	Arm	Panel, Wall, Stand and Arm VESA 100 x 100 mm		
Operating Temperature			-10°C ~ 50°C	(with air flow)		
Storage Temperature		-20°C ~ 60°C				
IP Level			IP 65 complia	ant front panel		
Power Supply			12V D	C input		

Heavy Industrial Monitor







Model Name	DM-F65A	DM-F08A	DM-F12A	DM-F15A	
LCD Display	6.5" (4:3)	8" (4:3)	12" (4:3)	15" (4:3)	
Max. Resolution	640 (W) x 480 (H)	800 (W) x 600 (H)	1024 (W) x 768 (H)	1024 (W) x 768 (H)	
Touchscreen & Controller	5-wire resistive single touc	h window / Penmount 6000	5-wire resistive single touch window / Penmount 6000 10-point projected capacitive touch window / EETI EXC3000		
I/O Ports	1 x VGA (DB-15) 1 x DVI 1 x USB 2.0 (touch) 1 x RS-232 (reserved fo 1 x Lockable 12V DC ja	r resistive touch ATO) ck	1 x VGA (DB-15) 1 x HDMI 1 x DisplayPort 1.1 1 x USB 2.0 (touch)	1 x RS-232 (reserved for resistive touch ATO) 1 x Lockable 9V-36V DC jack 1 x 9V-36V terminal block	
Construction Material		Aluminum front frame an	d sheet metal rear cover		
Mounting	Panel Mount/ Rack Mou	nt/ 75 x 75 VESA Mount	Panel Mount/ Rack Mount/ 100 x 100 VESA Mount		
Operating Temperature	-20°C ~ 60°C	(with air flow)	-20°C ~ 60°C		
Storage Temperature	-20°C ~ 70°C				
IP Level	IP 65 compliant front panel				
Power Input	12V	DC	9V ~ 36V DC		







Model Name	DM-F17A	DM-F19A	DM-F22A	DM-F24A		
LCD Display	17" (5:4)	19" (5:4)	21.5" (16:9)	24" (16:9)		
Max. Resolution	1280 (W) x 1024 (H)	1280 (W) x 1024 (H)	1920 (W) x 1080 (H)	1920 (W) x 1080 (H)		
Touchscreen & Controller	5-wire resistive single touc 10-point projected capacitive t	h window / Penmount 6000 couch window / EETI EXC3000	10-point projected capacitive touch window / EETI EXC3000	10-point projected capacitive touch window / EETI EXC3000		
I/O Ports	1 x VGA (DB-15) 1 x DVI (F19A only) 1 x HDMI (F17A only) 1 x DisplayPort 1.1 1 x USB 2.0 (touch) 1 x RS-232 (reserved f 1 x Lockable 9V-36V D 1 x 9V-36V terminal blo	or resistive touch ATO) C jack cck	1 x VGA (DB-15) 1 x HDMI 1 x DisplayPort 1.1 1 x USB 2.0 (touch) 1 x RS-232 (reserved for resistive touch ATO) 1 x Lockable 9V-36V DC jack 1 x 9V-36V terminal block			
Construction Material		Aluminum front frame ar	nd sheet metal rear cover			
Mounting	Panel Mount/ Rack Mount/ 100 x 100 VESA Mount	Panel Mount/ Rack Mount 100 x 100 VESA Mount	Panel Mount/ 100 x 100 VESA Mount	Panel Mount/ 100 x 100 VESA Mount		
Operating Temperature	-20°C ~ 60°C (with air flow)		-10°C ~ 50°C (with air flow)	-10°C ~ 50°C (with air flow)		
Storage Temperature	-20°C ~ 70°C		-20°C ~ 60°C	-20°C ~ 60°C		
IP Level	IP 65 compliant front panel					
Power Input		9V ~ 36V DC				

• Vertical Market Panel PC





Model Name	UPC-F12C-ULT3	INOX-F15C-ULT3
LCD Size	12.1"	15"
Resolution	1024 (W) x 768 (H)	1024 (W) x 768 (H)
Touchscreen	P-CAP / Resistive Touch	P-CAP / Resistive Touch
CPU	6 th Generation Intel [®] Core [™] i5 and Celeron [®] ULT processor	6 th Generation Intel [®] Core [™] i5 and Celeron [®] ULT processor
I/O Ports and Switches	M12 Type: 1 x 5-pin M12 connector for DC jack (12 ~ 36V DC) 1 x 8-pin M12 connector for GbE LAN 1 x 8-pin M12 connector for RS-232 1 x 8-pin M12 connector for RS-232/422/485 2 x 8-pin M12 connector for two USB 2.0 Standard Type: 1 x DC in terminal block (12V-36V DC) 1 x DC jack (12V-36V DC) 1 x DC jack (12V-36V DC) 1 x HDMI 1 x RS-232 (COM1 RJ-45) 1 x RS-232/422/485 (COM2 RJ-45) 1 x VGA 2 x LAN 2 x USB 2.0 2 x USB 3.2 Gen 1	1 x 5-pin M12 connector for DC jack (9-36V DC) 1 x Power switch with power LED indicator 1 x Pressure relief valve 2 x 8-pin M12 connector for RS-232/422/485 2 x 8-pin M12 connector for two USB 2.0 2 x 8-pin M12 X-Code connector for GbE LAN
System Cooling	Fanless	Fanless
Operating Temperature	-20° C ~ 60° C (without heater solution) - 40° C ~ 60° C (with heater solution)	-20°C ~ 50°C
Storage Temperature	-40°C ~ 70°C	-30°C ~ 60°C
IP Rating	Full IP65 or Full IP 66 (with M12 connectors)	Front IP 69K/ Others IP 66

• Industrial PDA



Model Name		MODAT-550A
	LCD size	5.5"
Display	Max Resolution	1080 x 1920 (Full HD)
	Touchscreen	5-point capacitive
0	CPU	Octa-core 64-bit Cortex-A53 1.5 GHz processor
System	Operating System	Android 7.0
	USB	1x High-speed Micro USB 2.0 OTG
	Micro HDMI	N/A
I/O Internace	Audio	1 x 0.5W speaker 1 x Headset/Mic-in
	Expansion	N/A
D	Power Adapter	5V/3A
Power	Battery	4000 mAh
	Operating Temperature	-10°C ~ 50°C
Environment	Storage Temperature	-20°C ~ 60°C
	Environmental Protection	IP 65

• TANK AloT Developer Kit



	DX U P				
Model Name	TANK-870AI				
CPU	Intel [®] Xeon [®] E3-1268LV5 2.4GHz (up to 3.4GHz, quad core, TDP=35W) Intel [®] Core™ i7-7700T 2.9GHz (up to 3.8GHz, quad core, TDP=35W) Intel [®] Core™ i5-7500T 2.7GHz (up to 3.3GHz, quad core, TDP=35W) Intel [®] Core™ i5-6500TE 2.4 GHz (up to 3.4GHz, quad core, TDP=35W) Intel [®] Core™ i5-6500TE 2.3 GHz (up to 3.3GHz, quad core, TDP=35W)				
RIS Solution	1 x iRIS-2400 (optional)				
/O Interfaces	1 x HDMI/DP 1 x iDP (optional) 1 x Line-out 1 x Mic-in 1 x VGA 2 x RJ-45 (LAN1: Intel® I219LM PCIe controller/ LAN2 (iRIS): Intel® I210 PCIe controller)				
Expansions	1 x Half-size PCIe Mini slot 1 x Full-size PCIe Mini slot (supports mSATA, colay with SATA) 2 x PCIe x8 slot				
System Fan	Fanless				
Chassis Construction	Extruded aluminum alloy				
Power Input	DC jack: 9 V ~ 36 V DC Terminal Block: 9 V ~ 36 V DC				
Power Consumption	19 V@3.68 A (Intel [®] Core™ i7-6700TE with 8 GB memory)				
Mounting	Wall mount				
Dperating Femperature	$ \begin{array}{llllllllllllllllllllllllllllllllllll$				
Neight (Net/Gross)	4.2 kg/6.3 kg				

• Embedded System







Model Name	TANK-880-Q370	TANK-870-Q170	TANK-870e-H110	FLEX-BX200-Q370
СРИ	8 th Gen Intel [®] Core [™] CPU & Intel [®] Core [™] i7-9700TE 1.8GHz (up to 3.8GHz, 8-core, TDP 35W) Intel [®] Core [™] i5-9500TE 2.2GHz (up to 3.6GHz, 6-core, TDP 35W)	7 th Gen Intel [®] Core [™] CPU & Intel [®] Core [™] i7-6700TE (2.4 GHz, quad-core, TDP=35W) Intel [®] Core [™] i5-6500TE (2.3 GHz, quad-core, TDP=35W)		8 th /9 th Genertion Intel [®] Core ™ i7/i5/i3 porcessors in the LGA 1151(Max. 65W) Intel [®] 300 Series Chipsets Q370
iRIS Solution	N/A	1 x iRIS-2400 (optional)	N/A	N/A
I/O Interfaces	1 x HDMI 1 x DP 1 x Line-out 1 x Line-out 1 x Mic-in 3 x RJ-45 (1 x PCIe GbE by Intel [®] I219 controller) 2 x PCIe GbE by Intel [®] I210 controller) 3 x RS-232/422/485 (DB-9 w/ isolation) 6 x USB 3.2 Gen 1 8-bit DIO (4-in/4-out) 4 x 2.5" HDD/SSD SATA 66b/s bay (with RAID 0/1/5/10 support) 1 x TPM pin header (2x10 pin)	1 x HDMI/DP 1 x iDP (optional) 1 x Line-out 1 x Mic-in 1 x VGA 2 x RJ-45 (LAN1: Intel® I219LM PCIe controller LAN2 (iRIS): Intel® I210 PCIe controller) 2 x RS-232(422/485 (DB-9) 4 x RS-232 (2 x RJ-45, 2 x DB-9 w/ isolation) 4 x USB 2.0 4 x USB 3.2 Gen 1	1 x HDMI 1.4 1 x Line-out 1 x Mic-in 1 x VGA 2 x RJ-45 PCIe GbE by RTL8111G controller 2 x RS-232/422/485 (DB-9, w/ isolation) 4 x USB 3.2 Gen 1	1 x AC power in inlet 1 x HDMI output 1 x Line out 1 x Mic in 2 x GbE LAN 2 x RS-232 DB-9 type 6 x USB 3.2 Gen 1 Type-A
Expansions	1 x Full-size PCIe Mini slot (PCIe x1 / USB 2.0 / SATA) 1 x 2230 A key (PCIe x2 / USB 2.0) 2 x 2280 M key (PCIe x2) 1 x PCIe x 16 / 1 x PCIe x1/ 2 x PCIe x4	1 x Half-size PCle Mini slot 1 x Full-size PCle Mini slot (supports mSATA, colay with SATA) 2-slot model: 1 x PCle x16, 1 x PCl 2-slot model: 2 x PCle x8 4-slot model: 2 x PCle x8, 2 x PCl, 1 x Full-size PCle Mini 4-slot model: 1 x PCle x16, 3 x PCl, 1 x Full-size PCle Mini	1 x Full-size PCIe Mini slot 1 x Full-size PCIe Mini slot (supports mSATA, colay with SATA) 3A: 1 x PCIe x16, 2 x PCI 3B: 1 x PCIe x16, 1 x PCIe x4, 1 x PCI 3C: 3 x PCI	1 x 2230 M.2 A key (PCle x1/USB 2.0) 1 x 3042 M.2 B key (PCle x1/USB 3.2 Gen 1) 1 x 2280 M.2 M key (PCle x4) 2 x PCle 3.0 x 4 2 x PCle 3.0 x 8
System Fan		Fanless		Active fan
Chassis Construction		Extruded aluminum alloy		Metal housing
Power Input	DC jack: 9 V ~ 36 V DC Terminal block: 9 V ~ 36 V DC		DC jack: 9 V ~ 36 V DC Terminal block: 9 V ~ 36 V DC	115VAC~230VAC, 50/60Hz
Power Consumption	19V @ 3.6A (Intel [®] Core ™ i7-8700T with 8GB memory)	19 V@3.68 A (Intel® Core™ i7-6700TE with 8 GB memory)	19 V@3.44 A (Intel® Core™ i7-6700TE with 8 GB memory)	115VAC@1A, 230VAC@0.5A
Mounting	Wall mount		Wall mount & DIN Rail	Wall mount / RACK moynt
Operating Temperature	-20°C ~ 60°C with air flow (SSD), 10% ~ 95%, non-condensing	i7-6700TE: -20°C ~ 45°C with air flow (SSD) i5-6500TE: -20°C ~ 60°C with air flow (SSD)	i7-6700TE: -20°C ~ 50°C with air flow (SSD) i5-6500TE: -20°C ~ 60°C with air flow (SSD)	-20°C ~ 50°C (with SSD and TDP 65W processor) -20°C ~ 40°C (with HDD or add-on cards without fan)
Weight (Net/Gross)	ht (Net/Gross) 5.4 kg/8.45 kg 2-slot: 4.2 kg/6.3 kg / 4-slot: 4.5 kg/6.5 kg		2.8 kg/4.3 kg	4 kg/6 kg







Model Name	FLEX-BX100-ULT5	IVS-300-BT / IVS-300-ULT3	IVS-110-AL
CPU	8 th Genertion Intel [®] Core [™] i5-8365U 4.10GHz 8 th Genertion Intel [®] Celeron [®] 4205U 2.00GHz	Intel [®] Celeron [®] J1900 processor (quad-core 2GHz, 10W TDP) or Intel [®] Core [™] i5-6300U processor (dual-core, 2.4 GHz, 15W TDP)	Intel [®] Atom™ x7-E3950 processor (quad-core 1.6GHz, 12W TDP)
iRIS Solution	N/A	N/A	N/A
IVO Interfaces 4 x USB 3.2 Gen.1 1 x HDMI output 1 x RS-232/422/485 1 x RS-232 1 x GbE LAN 2 x PoE GbE LAN (IEEE802.3af/at/bt) 1 x 12V DC jack 1 x AT/ATX switch		1 x 3G 1 x BT 1 x DB-15 isolated RS-422/485 1 x DB9 CAN-Bus/OBD-II 1 x GPS 1 x HDMI 1 x Line-out 1 x Mic-in 1 x VGA 1 x WI-Fi 2 x DB-9 RS-232 2 x On-board SIM card slot 2 x USB 3.2 Gen 1 4 x RJ-45 PCIe GbE by Intel® I210-AT support POE IEEE802.3af (Each port max 15.4W)	1 x 16-bit digital I/O (8-bit in/8-bit out) 1 x DB-9 OBD-II/J1939 1 x HDMI 1 x Line-out 1 x RJ-45 PCIe GbE by Intel® I211 1 x RS-232/422/485 1 x VGA 2 x On-board SIM card slot 4 x USB 3.2 Gen 1
System Fan	Fanless	Fanless	Fanless
Chassis Construction	Sheet metal	Extruded aluminum alloy	Extruded aluminum alloy
Power Input	DC jack: 12 V DC	Cigarette lighter power cable: 9 V ~ 36 V DC	Cigarette lighter power cable: 9V~36V DC
Power Consumption	12 V@2.2 A (Intel [®] Core [™] i5-8365U with 4 GB DDR4 memory)	12 V@14 A (Intel® i5-6300U with 4 GB DDR4 memory + 4 PoE)	12V @ 5A (Intel [®] Atom™ x7-E3950 CPU with 8GB DDR3L memory)
Mounting	Wall mount	Wall mount	Mounting kit & VESA mount
Operating Temperature	-10°C ~ 50°C (with air flow)	-20°C ~ 60°C with air flow	-30°C ~ 70°C with air flow
Weight (Net/Gross)	3 kg/4.5 kg	3 kg/4.5 kg	2.4 kg/3.8 kg









Model Name	DRPC-230-ULT5	DRPC-130-AL	DRPC-120-BT	ITG-100-AL	ulBX-250-BW
CPU	Intel [®] Core ™ i5-8265U 1.6GHz (up to 3.9 GHz)	Intel®Atom™ E3930 1.8GHz	Intel® Atom™ E3845 1.91GHz	Intel [®] Atom™ x5-E3930 1.3 GHz (up to 1.8GHz, dual-core, TDP=6.5W)	Intel [®] Celeron [®] N3160 (up to 2.24GHz, quad-core, 2 MB cache, TDP=6W)
iRIS Solution	N/A	N/A	1 x iRIS-2400 (optional)	N/A	N/A
I/O Interfaces	1 x HDMI 1 x DP 3 x RJ-45 (1 x PCIe GbE by Intel®1219 controller, 2 x PCIe GbE by Intel®1211 controller) 4 x RS-232/422/485 (DB-9) 2 x RS-232 (RJ-45) 4 x USB 3.2 Gen 2 (10Gb/s) 8-bit DIO (4-in/4-out) 1 x TPM pin header (2x10 pin)	1 x DB-9 w/ 2.5kV isolation protection supporting 2-port CAN-bus 1 x Internal on-board SIM slot (optional) 1 x TPM 2.0 (2x10 pin, optional) 2 x HDMI 1.4b 2 x RJ-45 (PCIe GbE by Intel® I211 controller) 4 x RS-232/422/485 (DB-9) 4 x USB 3.2 Gen 1	1 x HDMI 1 x VGA 2 x RJ-45 1 x PCIe GbE by Intel® I210 controller 1 x PCIe GbE by Intel® I211 controller 2 x RS-232 (DB-9 w/3KV isolation protection*) 2 x RS-422/485 (DB-9 w/3KV isolation protection*) 2 x USB 2.0 2 x USB 2.0 2 x USB 3.2 Gen 1	1 x AT/ATX switch 1 x VGA 1 x Power button 1 x Reset button 1 x VGA 2 x RJ-45 PCIe GbE by Intel® I211 controller 2 x RS-232/422/485 2 x USB 3.2 Gen 1	1 x AT/ATX switch 1 x HDMI 1 x Line-out 1 x Mic-in 1 x Power button 1 x Reset button 1 x VGA 2 x RJ-45 PCIe GbE by Intel® I211 controller 2 x RS-232/422/485 (RJ-45) 4 x USB 3.2 Gen 1
Expansions	1 x Full-size PCIe Mini slot (PCIe x1 / USB 2.0 / SATA) 1 x 2230 A key (PCIe x1 / USB 2.0) 1 x PCIe x4	1 x Full-size PCIe Mini slot 1 x Full-size PCIe Mini slot (supports mSATA, colay with SATA)	1 x Half-size PCIe Mini slot (w/o USB signal) 1 x Full-size PCIe Mini slot (supports mSATA, colay with SATA)	M.2: 1 x M.2 2230 (A key, PCIe by 1, USB 2.0) PCIe Mini: 1 x Full-size PCIe Mini slot (supports mSATA, colay with SATA)	1 x Full-size PCIe Mini slot (supports mSATA, colay with SATA)
System Fan	Fanless	Fanless	Fanless	Fanless	Fanless
Chassis Construction	Extruded aluminum alloy	Extruded aluminum alloy	Extruded aluminum alloy	Extruded aluminum alloy	Extruded aluminum alloy
Power Input	12-24V DC-in 3-pin terminal block: 12 V ~ 24 V DC 3-pin terminal block: 9 V ~ 30 V DC		3-pin terminal block: 9 V ~ 30 V DC	2-pin terminal block: 12 V DC	DC jack: 12 V DC
Power Consumption	12V @ 4.98A	12V @ 2.88 A (Intel [®] Atom ™ x5-E3930 CPU with 4GB 1600 MHz DDR3L memory)	12 V@ 2.1 A (Intel® Atom™ E3845 with 2 GB memory)	12V @ 1A (Intel [®] Atom [™] E3930 with 2GB memory)	12 V@2 A (Intel® Celeron® N3160 with 2 GB memory)
Mounting	DIN-rail	DIN-rail / Wall mount	DIN-rail	DIN-rail / Wall mount	Wall mount, VESA 75
Operating Temperature	-20°C ~ 60°C with air flow (SSD), 10% ~ 95%, non- condensing	-20°C ~ 60°C with air flow (SSD)	-20°C ~ 60°C with air flow (mSATA)	-20°C ~ 60°C with air flow (SSD)	-20°C ~ 60°C with air flow (SSD)
Weight (Net/Gross)	2.9 kg	1.4Kg/2.5Kg	1.4 kg/2.5 kg	ITG-100-AL-E1/S: 0.67 kg/1.03 kg ITG-100-AL-E1: 0.86 kg/1.22 kg	470 g/1.4 kg

* COM port isolation: 3 kV for 1 sec, 2.5 kV for 1 minute

• Transportation System

Model Name	IKARPC-07A-BT	AFOKAR-08A	IKARPC-W10A-BT
LCD Size	7"	8"	10.1"
Resolution	1024 × 3 (RGB) × 600	800 (RGB) × 1280	1280 x 800
Touchscreen	Projected capacitive touch with USB interface	Projected capacitive touch with AG coating	Projected capacitive touch with USB interface
СРИ	Intel [®] Atom™ processor E3826 (dual-core, 1.46 GHz, 7W)	Rockchip RK3399 (dual-core Cortex-A72 up to 1.8GHz + quad-core Cortex-A53 up to 1.5GHz)	Intel [®] Atom™ processor E3826 (dual-core, 1.46 GHz, 7W)
Expansions PCle Mini	1 x Full-size PCIe Mini (reserved for mSATA module), 1 x Full-size PCIe Mini (reserved for WWAN module), 1 x Half-size PCIe Mini (reserved for WLAN module)	1 x Full-size PCIe Mini (reserved for WWAN)	1 x Full-size PCIe Mini (reserved for WWAN module), 1 x Full-size PCIe Mini (reserved for WLAN module)
System Fan	Fanless	Fanless	Fanless
Chassis Construction	PC + ABS plastic	PC + ABS plastic front, Metal rear	PC + ABS plastic
Power Input	Cigarette lighter power cable, DC 9 V ~ 30 V	Cigarette lighter power cable, DC 9 V ~ 30 V	Cigarette lighter power cable, DC 9 V \sim 30 V
Power Consumption	12V @ 1.25 A	12V @ 1.2A	12 V @ 1.73 A
Mounting	VESA 75	VESA 75	VESA 100
Operating Temperature	-20°C ~ 60°C with air flow	-10°C ~ 50°C with air flow	-20°C ~ 60°C with air flow

• Industrial Motherboard







		Carl P		
Model Name	IMBA-Q370	IMBA-Q170-i2	IMBA-H110	
CPU Socket	LGA1151	LGA1151	LGA1151	
СРИ Туре	8 th /9 th generation Intel [®] Core ™ i9/i7/i5/i3, Pentium [®] or Celeron [®] processor	6 th /7 th generation Intel [®] Core™ i7/i5/i3 Pentium [®] and Celeron [®] processor	6 th /7 th generation Intel [®] Core™ i7/i5/i3 Pentium [®] and Celeron [®] processor	
Display Interface	Triple independent display support 1 x DP++ 1 x VGA 1 x HDMI 1 x Internal DisplayPort	Triple independent display support 1 x HDMI 2.0 1 x VGA 1 x DVI-D 1 x iDP interface	Dual independent display support 1 x DVI-I 1 x iDP 1 x HDMI1.4	
iRIS	N/A	1 x iRIS-2400 slot	N/A	
I/O Interface	1 x PS/2 KB/MS 2 x RS-232/422/485 2 x USB 3.2 Gen 2 4 x RS-232 4 x USB 3.2 Gen 1 6 x USB 2.0 6 x SATA 6G/s (RAID 0/1/5/10 supported)	1 x KB/MS 1 x LPT 2 x RS-232/422/485 5 x USB 3.2 Gen 1 4 x RS-232 7 x USB 2.0	1 x KB/MS 1 x LPT 2 x RS-232/422/485 4 x USB 3.2 Gen 1 4 x RS-232 5 x USB 2.0	
Dimensions	244 mm x 305 mm	244 mm x 305 mm	244 mm x 305 mm	
Weight	GW: 1200g / NW: 700g	GW: 1200g / NW: 700g	GW: 1200g / NW: 700g	

Al Accelerator Card







Model Name	Mustang-F100-A10	Mustang-V100-MX8
Main Chip	Intel [®] Arria [®] 10 GX1150 FPGA	Eight Intel [®] Movidius™ Myriad™ X MA2485 VPU
Deep Learning Tool	Intel [®] Distribution of OpenVINO™ toolkit	
Memory	8G On-board DDR4	4G On-board DDR4
Dataplane Interface	PCI Express 3.0 x8	PCI Express 2.0 x4
Power Consumption	<60W	<30W
Operating Temperature 5°C~60°C (ambient temperature)		5°C~55°C (ambient temperature)
Cooling	Active fan	Active fan
Dimensions Standard Half-Height, Half-Length, Double-slot		Half-Height, Half-Length, Single-slot PCIe
Power Connector	Preserved PCIe 6-pin 12V external power	Preserved PCIe 6-pin 12V external power
Dip Switch/LED Indicator	Identify card number	Identify card number

EtherCAT Motion Controller



Dimension	115 x 115 x 35 mm Fanless design	59.4 x 140 x 171.5mm Fanless design	121.5 x 255.2 x 205 mm Fanless design
Axes	8	16	32
Command Cycle	1ms	1ms	1ms
CPU	Vortex 86DX3 Dual-core, 1GHz	Intel [®] Celeron [®] J1900	Intel [®] Core™ i7-6700TE Intel [®] Core™ i5-6500TE

Integrated Motion Controller



Model Name	MDH-1000	MDH-1500	MDH-1800
Dimension	301 x 219 x 60mm Fanless design	301 x 219 x 60mm Fanless design	221 x 93 x 175mm
Axes	8-axis pulse motor control supporting dual-mode control (4-axis servo/step motor and 4-axis step motor.)	8 axes of pulse type motor control interfaces supporting servo/step dual mode, and one axis Encoder input interface	8-axis pulse motor control; standard for 4-axis, the other 4-axis is for optional.
CPU	Intel [®] Bay Trail J1900, Quad-core, 2.41GHz, 10W	Intel [®] Bay Trail J1900, Quad-core, 2.41GHz, 10W	Intel [®] Core [™] i7: 4790s Intel [®] Core [™] i5: 4590s Intel [®] Core [™] I3: 4330

Intelligent Motion Controller



• I/O Expansion Module



Input/ Output	16photocouplerisolated Inputs, 16photocouplerisolated Open Collector outputs	32photocouplerisolated inputs, 32photocouplerisolated OpenCollector outputs	32photocouplerisolated inputs, 32photocouplerisolated OpenCollector outputs
Interface	RS-485	Ethernet	Ethernet
Protocol	MODBUS/RTU	EtherCAT	Ethernet
Connector	DB-9 Male	RJ-45	RJ-45



Headquarters 威強電工業電腦 IEI Integration Corp.

 No. 29, Zhongxing Rd., Xizhi Dist., New Taipei City 221, Taiwan
 138 University Parkway, Pomona, CA 91768

 TEL: +886-2-86916796 / +886-2-26902098
 FAX : +886-2-66160028
 TEL : +1-909-595-2819
 FAX : +1-909-595-2816

 sales@ieiworld.com
 www.ieiworld.com
 sales@usa.ieiworld.com
 usa.ieiworld.com

America IEI Technology USA Corp. 138 University Parkway, Pomona, CA S

*Specifications are subject to change without prior notice.

China 威强电工业电脑 IEI Integration (Shanghai) Corp. 上海市闵行辈庄工业区审富路515号 515, Shen Fu Rd., Xin Zhuang Industrial Develop Zone, Shanghai, 201108, China TEL:+86-21-3116-7799 FAX:+86-21-3462-7797 sales@ieiworld.com.cn www.ieiworld.com.cn